resideo

5800 Series

Door/Window Transmitters

Honeywell Home



5800MINIV
5800MINIVBR



5814



5815/5815WG



5816

resideo



5817XT



5817CBXT



5818MNL



5820L

The Honeywell Home 5800 Series of door and window wireless transmitters provide the most reliable, convenient, and cost -effective solutions for security protection. Powerful and versatile, these devices have been designed to solve the toughest, most labor-intensive installations—saving time and money.

With a demonstrated outdoor range of over a mile, the 5800 Series wireless transmitters are the best-performing in the industry.

Features & specifications

5800MINIV Door/Window Contact
The 5800MINIV features a sleek, compact design; making it an ideal choice for ornate doors, windows, and casements.

- Single-zone transmitter
- Sleek design
- Transmits supervisory, tamper, and low battery
- Case tamper protection
- Magnet included
- Ideal for double-hung windows
- 3VDC Coin Cell (CR2450) battery included
- Sensor dimensions:
  0.45"H x 1.25"W x 2.44"L
  (11.5mm H D x 32mm W x 62mm L)
- Magnet dimensions:
  0.38"H x 0.41"W x 1.49"L
  (9.5mm H x 10.5mm W x 37.9mm L)
- ETL Listed
- Operating wireless frequency: 345 MHz

5814 Ultra Small Door/Window Transmitter
The 5814 provides the perfect solution for difficult-to-reach places and applications where aesthetics and small size are important.

- Ideal for ornate doors/windows, casements, etc.
- Extremely compact
- Built-in reed switch and tamper
- Includes a supervised, replaceable CR2430 battery
- Dimensions: 1-1/2" H x 1-3/16" W x 5/8" D
  (38.1mm x 30.2mm x 15.9mm)

5815 Door/Window Transmitter
The 5815 is the ideal solution for installations where small size and aesthetics are important. It provides a reliable, convenient, and cost-effective solution for door and window protection.

- New sleek design
- Two reed switches
- Transmits supervisory, tamper and low battery messages
- Includes a supervised replaceable CR123 battery
- Dimensions: 3" H x 1-1/2" W x 7/8" D
  (76.2mm x 38.1mm x 22.2mm)
- UL listed

5815WG Door/Window Transmitter
When you need extra gap on an installation, select the 5815WG.

- Sleek design
- Wide gap contact over 1.0"
- Single reed switch
- Aux terminals for wired devices
- Includes supervised, replaceable CR123 battery
- Dimensions: 3" H x 1-1/2" W x 7/8" D
  (76.2mm x 38.1mm x 22.2mm)
- UL Listed

5816 Door/Window Transmitter
The 5816 is a two-zone transmitter with both built-in magnetic reed switches and a wired closed-circuit contact loop.

- Features a standard white plastic case. Brown cases available in packs of three (5816BR).
- Includes a supervised replaceable CR123 battery
- Four pack of spare magnets (5899)
- Dimensions:
  3-1/16" H x 1-9/16" W x 1-3/16" D
  (77.8mm x 39.7mm x 30.2mm)
- UL listed
- Operating wireless frequency: 345 MHz

5800 - Door/Window Transmitters

Features & specifications

5817CBXT Wireless Light Commercial Transmitter
The 5817CBXT is a universal contact-monitoring transmitter that can be used with household and light commercial fire and burglary-initiating devices.

- The 5817CBXT has four unique input loops (zones)
- The first loop (primary loop) is supervised and typically used for high-priority alarm reporting such as light-commercial fire or burglary
- The second loop is the built-in, normally closed reed switch used in conjunction with a magnet
- The third loop is another normally closed household burglary loop
- A fourth (automatically enrolled) loop contains two tamper switches to protect the 5817CBXT
- Dimensions: 3-1/2" H x 1-9/16" W x 1-3/16" D (88.9mm x 39.7mm x 30.2mm)
- UL listed

5817XT Three Zone Universal Transmitter
5817XT Three zone transmitter with three separate contact loops. Primary loop supports normally open and normally closed applications and fast loop response time. The two auxiliary loops support conventional normally closed contact applications.

- Features a normal zone response time of 200msec; the fast zone response is 5msec
- Includes a supervised replaceable CR123 battery
- Dimensions: 3-1/2" H x 1-9/16" W x 1-3/16" D (88.9mm x 39.7mm x 30.2mm)
- UL Listed

5818MNL Recessed Door/Window Transmitter
The 5818MNL is a magnetic contact sensor that provides concealed protection for doors or windows.

- Includes self-contained transmitter and reed sensor
- Virtually disappears once installed
- Easy replaceable AAA lithium battery
- 0.5" gap (transmitter to magnet)
- Features a tapered cylinder for easy and flush fit
- Dimensions: 0.75" (19.05mm) diameter x 3.0" (76.2mm) length
- UL listed

5820L Door/Window Contact Transmitter
The 5820L is nearly half the size of standard door/window transmitters. It is ideal for casement and double-hung windows.

- Sleek design is nearly half the size of competitors
- Case tamper protection (front and back)
- Ideal for double-hung windows
- Easy replaceable AAA lithium battery
- Dimensions: 3.0" H x 0.5" W x 0.8" D (76.2mm x 12.7mm x 20.3mm)
- UL listed

Ordering Information

Product	Description
5800MINIV	Door/Window Contact with lithium battery (white & brown)
5814	Ultra Small Door/Window Transmitter
5815/5815WG	Door/Window Transmitter
5816	Door/Window Transmitter
5817XT	Three Zone Universal Transmitter

Product	Description
5817CBXT	Wireless Light Commercial Transmitter (UL Light Commercial Approved for Fire and Burglary)
5818MNL	Recessed Door Transmitter with lithium battery supplied
5820L	Slimline Door/Window Contact Transmitter supplied with lithium battery
5899	Four pack of spare magnets for 5816

For more information
resideo.com/pro

Resideo Technologies, Inc.
16100 N 71st Street, Suite 550
Scottsdale, Arizona 85254
Office: 480.573.5340

L/5800TRAND/D | AR | 04/26
© 2026 Resideo Technologies, Inc.
All rights reserved. The Honeywell Home trademark is used under license from Honeywell International, Inc.
These products are manufactured by Resideo Technologies, Inc., and its affiliates.