Honeywell Home

5800MINIV

Wireless Door/Window Contact

The Honeywell Home 5800MINIV provides all of the advantages of the field-proven, quick-install 5800 Series wireless devices, with the addition of signal transmission and check. It blends in with any decor, making it ideal for applications with aesthetic needs such as ornate doors, casements, and double-hung windows.

The 5800MINIV provides a check and installs easily on doors or windows with the included double-sided adhesive tape.



5800MINIV



5800MINIVBR

Features & Benefits

- Compact and unobtrusive design—ideal when aesthetics count
- Easy-to-open case requires no special tools
- Case tamper protection
- Ideal for double-hung windows
- Available in both white and brown to match any decor

Technical specifications

Sensor Dimensions:
0.45" H x 1.25" W x 2.44" L
(11.5mm H D x 32mm W x 62mm L)

Magnet Dimensions:
0.38"H x 0.41"W x 1.49"L
(9.5mm H x 10.5mm W x 37.9mm L)

Power Source: 3V lithium battery (supplied)

Maximum Mounting Gap:
Wood Surfaces: 1.0" (25.4mm)
Metal Surfaces: 0.5" (13.2mm)

Operating Temperature:
32°F to 122°F (0° C to 50°C)

Transmit Frequency: 345 MHz

Compatibility: Compatible with all 5800 Series wireless devices

Agency Listings: FCC, IC

Ordering information

Product title	Features
5800MINIV	Wireless Door/Window Contact supplied with lithium battery (White)
5800MINIVBR	Wireless Door/Window Contact supplied with lithium battery (Brown)

Resideo Technologies, Inc.
16100 N 71st Street, Suite 550
Scottsdale, Arizona 85254
Office: 480.573.5340

L_5800MNVC_D | AR | 04/26
© 2026 Resideo Technologies, Inc. All rights reserved.
The Honeywell Home trademark is used under license from Honeywell International, Inc.
These products are manufactured by Resideo Technologies, Inc., and its affiliates.